

NAME

Pod::Simple::PullParserEndToken -- end-tokens from Pod::Simple::PullParser

SYNOPSIS

(See *Pod::Simple::PullParser*)

DESCRIPTION

When you do `$parser->get_token` on a *Pod::Simple::PullParser*, you might get an object of this class.

This is a subclass of *Pod::Simple::PullParserToken* and inherits all its methods, and adds these methods:

`$token->tagname`

This returns the tagname for this end-token object. For example, parsing a "`=head1 ...`" line will give you a start-token with the tagname of "head1", token(s) for its content, and then an end-token with the tagname of "head1".

`$token->tagname(somestring)`

This changes the tagname for this end-token object. You probably won't need to do this.

`$token->tag(...)`

A shortcut for `$token->tagname(...)`

`$token->is_tag(somestring)` or `$token->is_tagname(somestring)`

These are shortcuts for `$token->tag() eq somestring`

You're unlikely to ever need to construct an object of this class for yourself, but if you want to, call `Pod::Simple::PullParserEndToken->new(tagname)`

SEE ALSO

Pod::Simple::PullParserToken, *Pod::Simple*, *Pod::Simple::Subclassing*

COPYRIGHT AND DISCLAIMERS

Copyright (c) 2002 Sean M. Burke. All rights reserved.

This library is free software; you can redistribute it and/or modify it under the same terms as Perl itself.

This program is distributed in the hope that it will be useful, but without any warranty; without even the implied warranty of merchantability or fitness for a particular purpose.

AUTHOR

Sean M. Burke sburke@cpantesters.org